TUBOMATIC H130 EL

CRIMPING (STANDARD VOLUME CRIMPING)

Code: TUBH130EL

Tubomatic H130 EL is ideal for crimping hydraulic hoses up to 1" ¼ six spirals and up to 2" four spirals.

MAIN FEATURES

- Ideal for crimping any type of fitting;
- New electronic device for managing the new electro-mechanical panel;
- Warning LED for possible anomalies in the system;
- Settable re-opening time after crimping;
- Settable crimping time.

◄ **ELECTRO-MECHANICAL CONTROL WITH ELECTRONIC DEVICE**

TECHNICAL DATA

CRIMPING FORCE	190 TON (210 US TONS)
6 SPIRALS 2 PIECES	1" 1/4
4 SP 2 PIECES	2"
INDUSTRIAL HOSE 2 PIECES	3"
MAX Ø	124 mm♦ (4.882")
CRIMPING/HOUR	780 ■
DIE OPENING	Ø + 35 mm (Ø + 1.378")
90° FITTING	2"
VOLTAGE	Any 60HZ 3PH/1PH
MOTOR POWER	4 Kw (5.5 Hp)
DIMENSIONS LxWxH	760x675x715 mm (29.921"x26.575"x28.149")
WEIGHT WITHOUT OIL	295 Kg (650 Lbs)
OIL	65 Lt.

INCLUDED ACCESSORIES

ELECTRO-MECHANICAL CONTROL WITH ELECTRONIC DEVICE	
VERNIER DIAL	

OPTIONAL

DISPENSER + PATENTED QUICK CHANGE	
BASE	
ELECTRIC PEDAL	
MARKING DIES (15 CHAR.)	
SPECIAL DIES	
BACK MIRROR	
CLEANING AND MAINTENANCE KIT	
SPECIAL VOLTAGE	SPECIAL

* WITH SPECIAL DIES Ø 104 MM UPON REQUEST | * THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE

Product specifications could be modified without prior notice.