

BC 1200 ECO and BC 1200 ECO WATER

Code: BC1200ECO - BC1200ECO/WATER

TESTING

PROVIDED WITH ONE Ø 1/4" GAS QUICK COUPLING AND PNEUMO-HYDRAULIC PUMP



WATER VERSION WITH CHAMBER AND COMPONENTS IN STAINLESS STEEL

MAIN FEATURES



Manually operated



Not suitable for burst test



Shock-proof testing windows



Water tests

BC 1200ECO/WATER

TECHNICAL DATA

| | |
|--|--------------------------------|
| STATIC PRESSURE | 1200 Bar (17400 Psi) |
| MIN. STARTING PRESSURE | 70 Bar (1015 Psi) |
| PRESSURE CONTROL | Manual |
| TEST | Manual |
| TYPE OF DRIVE | Pneumatic Intensifier |
| TESTING LIQUID | Fluid or water |
| N° MANIFOLDS | 1 |
| N° CONNECTIONS PER MANIFOLD | Special Quick Connection |
| LIQUID FILLING | Manual |
| PRESSURE PUMP FLOW | 0.3 Lt./min. (0.08 US gal/min) |
| PRESSURE DISCHARGE | Manual |
| STANDARD CHAMBER DIMENSIONS | 47.2"x21.6"x9.8" |
| BENCH DIMENSIONS | 59"x23.6"x47.2" |
| TANK | 30 Lt. (8 US gal) |
| WEIGHT WITHOUT OIL (BC 1200 ECO) | 364 Lbs |
| WEIGHT WITHOUT WATER (BC 1200 ECO WATER) | 286 Lbs |
| PRESSURE GAUGE | Analogic |

INCLUDED ACCESSORIES

SUCTION FILTER

DELIVERY FILTER

INTERNAL OIL PROTECTING MESH

ADAPTOR WITH QUICK COUPLING 1/4"

OPTIONAL

ADAPTOR: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"

PRESSURE REPORT KIT



ADAPTORS



ADAPTOR WITH QUICK COUPLING