

CENTER MAXI

Code: CENTERMAXI

MULTIFUNCTIONAL UNITS



CENTER JUNIOR

Code: CENJUUSFL

MULTIFUNCTIONAL UNITS



MINI CENTER

Code: CENECO

MULTIFUNCTIONAL UNITS



MAIN FEATURES



Bending



37° flaring



Deburring



DIN2353 rings
preassembly



Cutting



Electronic control



Ideal for volume
production



Equipped
with wheels



Equipped with
compressor for the
internal cleaning



Safety protections

CENTER MAXI
CENTER JUNIOR

CENTER MAXI

CENTER MAXI

CENTER JUNIOR

TECHNICAL DATA			
	CENTER MAXI	CENTER JUNIOR	MINI CENTER
24° PREASSEMBLY	6 → 42x4 mm on upper level	6 → 42x4 mm	6 → 42x4 mm
37° FLARING	1/4"→1"1/2 x 0.15" on upper level	1/4"→1"1/2 x 0.15"	1/4"→1"1/2 x 0.15"
BENDING Ø (GENERAL TUBE)	■ 1/4"→1"1/2	■ 1/4"→1"1/2 x 0.15"	1/4"→1"1/2 x 0.15"
BENDING Ø (AISI 316 TI)	1" 1/4 x 0.15" 1" 1/2 x 0.12"	-	-
BENDING Ø (ST 37.4)	1" 1/4 x 0.20" 1" 1/2 x 0.12"	-	-
MAX BENDING ANGLE	180°	-	-
90° BENDING TIME	6 Sec.	-	-
CUTTING (OD)	MAX Ø 4.9"	MAX Ø 3.9"	-
INT/EXT DEBURRING	6 - 42 mm (1/4"→1"1/2)	6 - 42 mm (1/4"→1"1/2)	6 - 42 mm (1/4"→1"1/2)
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
ELECTRONIC CONTROL	Touch Screen	-	-
DIMENSIONS LxWxH	55.1"x31.4"x59"	59.6"x39.3"x47.6"	28.3"x36.2"x50.9"
WEIGHT WITHOUT OIL	882 Lbs	672 Lbs	454 Lbs
STANDARD VOLTAGE	Any 60HZ 3PH	Any 60HZ 1PH	Any 60HZ 1PH
MOTOR POWER	MAX 4.5 Kw (6 Hp)	MAX 4.6 Kw (6.2 Hp)	MAX 1.7 Kw (2.3 Hp)
COMPRESSED AIR	-	220 Lt./Min. (58 US gal/Min.)	-
OIL	15 Lt. (4 US gal) not included	5 Lt. (1 US gal) not included	3 Lt. (0.8 US gal) included

OPTIONAL				
		C. M.	C. J.	M. C.
PEDAL FOR C50 ES		■	-	-
PEDAL FOR USFL 24/37 ES		■	-	-
TOOL HOLDER		included	■	■

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

■ With special tool Ø 5 mm upon request
Special equipment with different bending radius are available upon request

Product specifications could be modified without prior notice.