

**C42**  
Code: CURVC42

BENDING



**CMS42**  
Code: CURCMS42

BENDING



**M18**  
Code: CURVM18

BENDING



**MAIN FEATURES**



Ideal for volume production

C42



Electric limit switch

C42



Double effect manual pump

CMS42



Equipped with wheels

C42



Manually operated

CMS42  
M18

TECHNICAL DATA			
	C42	CMS42	M18
<b>BENDING</b>	1/4" → 1" 1/2 × 0.15"	1/4" → 1" 1/2 × 0.15"	1/4" → 5/8"
<b>MATERIALS</b>	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
<b>DIMENSIONS LxWxH</b>	26.7"x34.6"x35.8"	16.5"x30.7"x38.5"	28.3"x5.1"x4.9"
<b>WEIGHT WITHOUT OIL</b>	225 Lbs	90 Lbs	22 Lbs
<b>OIL</b>	5 Lt. (1 US gal) not included	included	-
<b>STANDARD VOLTAGE</b>	Any 60HZ 3PH/1PH	-	-
<b>MOTOR POWER</b>	1.1 Kw (1.5 Hp)	-	-

INCLUDED ACCESSORIES				
		C42	CMS42	M18
<b>MECHANICAL LIMIT SWITCH</b>		-	■	-
<b>BENDING TOOLS AND TOOL HOLDER</b>		-	-	■
<b>VICE FIXING PIN</b>		-	-	■

**EQUIPMENT SUITABLE TO PROCESS RIGID TUBES IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL**

MAX THICKNESS	
C42	
4 mm	Ø 38
3 mm	Ø 42

Ø	M18							
	6	8	10	12	14	15	16	18
<b>MEDIUM BENDING RADIUS</b>	33.5	33.5	36	36	36	43.5	43.5	51