

**SPF6**  
Code: SPELSPF6

SKIVING

SELF-CENTERING  
PNEUMATIC VICE



**SPF3**  
Code: SPELSPF3

SKIVING



**SPF2**  
Code: SPELSPF2

SKIVING



**MAIN FEATURES**



Simultaneous skiving

SPF6  
SPF3



Internal skiving

SPF3  
SPF2



External skiving

SPF3  
SPF2



Drawer for shavings



Ideal for volume production

SPF6



Pneumatic vice



Safety device which prevents from operating the machine when the casing is open

SPF6



Preassembly

SPF6



Safety protections

TECHNICAL DATA			
	SPF6	SPF3	SPF2
EXTERNAL SKIVING	3"	2"	2"
INTERNAL SKIVING	3"	2"	2"
INSERT CAPACITY	3"	-	-
SIMULTANEOUS INT-EXT SKIVING	2"	2"	-
REVOLUTIONS/MINUTE	300	200	300
PNEUMATIC INPUT	MAX 8 Bar (115 Psi)	MAX 7 Bar (100 Psi)	MAX 7 Bar (100 Psi) OPTIONAL
WORKING CYCLE	Semi-Automatic	Manual	-
WEIGHT	727 Lbs	319 Lbs	181 Lbs
DIMENSIONS LxWxH	41.3"x51.1"x43.3"	28.5"x31.8"x42.1"	25.5"x17.2"x42.7"
STANDARD VOLTAGE	Any 60HZ 3PH	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH
MOTOR POWER	1.1 Kw (1.5 Hp)	0.75 Kw (1 Hp)	0.75 Kw (1 Hp)

ACCESSORIES				
		SPF6	SPF3	SPF2
ELECTRIC PEDAL (INCLUDED)		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
TOOL HOLDER		<input checked="" type="checkbox"/> included	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

SPF6



SKIVING MANDREL

SPF6



SELF-CENTERING  
PNEUMATIC VICE

SPF6



INSERT MANDREL

SPF3



SKIVING MANDREL

SPF2



SKIVING MANDREL

SPF2



PNEUMO-HYDRAULIC VICE  
OPTIONAL