

TF3
Code: TAGLTF3D
CUTTING



TF3 PI
Code: TAGLTF3DPI
CUTTING



TF2
Code: TAGLTF2D
CUTTING



MAIN FEATURES



Safety protections



Suction connection



Serrated blade



Ideal for your workshop



Recessed blade
for a greater safety



Pneumatic input

TF3 PI

TECHNICAL DATA

	TF3	TF3 PI	TF2
6 SPIRALS	2"	2"	1" 1/2
4 SPIRALS	2" 1/2	2" 1/2	2"
2 BRAIDS	3"	3"	2"
MAX Ø (OD)	3.9"	3.9"	2.9"
REVOLUTIONS/MINUTE	2900	2900	2900
BLADE Ø	400 mm (15.7")	400 mm (15.7")	250 mm (9.8")
STANDARD VOLTAGE	Any 60HZ 3PH	Any 60HZ 3PH	Any 60HZ 3PH/1PH
DIMENSIONS LxWxH	39.3"x27.9"x45.2"	40.3"x27.5"x45.2"	33"x21.6"x45.2"
WEIGHT	419 Lbs	530 Lbs	290 Lbs
MOTOR POWER	5.5 Kw (7.5 Hp) - A= 10.14	5.5 Kw (7.5 Hp) - A= 10.14	3 Kw (4 Hp)
PNEUMATIC INPUT	-	MAX 7 Bar (100 Psi)	-

ACCESSORIES

		TF3	TF3 PI	TF2
STROKE COUNTER		■	■	■
MEASURING HOSE HOLDER		■	■	■
CENTERING DEVICE + METER COUNTER (MAX 2")		■	■	■
MECHANICAL PEDAL CONTROL (INCLUDED)		■	-	■
PEDAL-EQUIPPED PNEUMATIC CONTROL (INCLUDED)		-	■	-
CUTTING SPEED ADJUSTMENT DEVICE (INCLUDED)		-	■	-