

TF6
Code: TAGLTF6D
CUTTING



TF5
Code: TAGLTF5D
CUTTING



TF4
Code: TAGLTF4D
CUTTING



MAIN FEATURES



Self-braking motor



Serrated blade



Self-centering hose support



Drawer for internal cleaning



Recessed blade for a greater safety



Safety protections



Touch-screen electronic control



Digital stroke counter

TF6

TF5
TF4

| TECHNICAL DATA | | | |
|--------------------------|-----------------------|---------------------------|---------------------------|
| | TF6 | TF5 | TF4 |
| 6 SPIRALS | 3" | 2" 1/2" | 2" |
| 4 SPIRALS | 3" | 3" | 2" 1/2" |
| 2 BRAIDS | 3" | 3" | 3" |
| INDUSTRIAL HOSE | 4" | 4" | 3" |
| MAX Ø (OD) | 6.2" | 6.2" | 3.9" |
| REVOLUTIONS/MINUTE | 2900 | 2900 | 2900 |
| PNEUMATIC INPUT | - | MAX 7 Bar (100 Psi) | MAX 7 Bar (100 Psi) |
| BLADE Ø | 650 mm (25.6") | 520 mm (20.4") | 400 mm (15.7") |
| STANDARD VOLTAGE | Any 60HZ 3PH | Any 60HZ 3PH | Any 60HZ 3PH |
| DIMENSIONS LxWxH | 49.2"x34.2"x63.5" | 48"x26.1"x62.5" | 44"x23.8"x57.2" |
| WEIGHT | 1027 Lbs | 860 Lbs | 717 Lbs |
| SELF BRAKING MOTOR POWER | 11 Kw (15 Hp) - A= 23 | 7.5 Kw (10 Hp) - A= 13.80 | 5.5 Kw (7.5 Hp) - A= 9.85 |

| ACCESSORIES | | | | |
|---|--|-----|-----|-----|
| | | TF6 | TF5 | TF4 |
| MEASURING HOSE HOLDER | | ■ | ■ | ■ |
| CENTERING DEVICE + METER COUNTER (MAX 2') | | ■ | ■ | ■ |
| FUME EXTRACTOR | | ■ | ■ | ■ |
| BLOWING KIT | | ■ | ■ | ■ |
| PEDAL-EQUIPPED ELECTRIC CONTROL (INCLUDED) | | ■ | - | - |
| PEDAL-EQUIPPED PNEUMATIC CONTROL (INCLUDED) | | - | ■ | ■ |
| CUTTING SPEED ADJUSTMENT DEVICE (INCLUDED) | | - | ■ | ■ |

TF6 ALSO AVAILABLE WITHOUT SELF-BRAKING MOTOR
Code: TAGLTF6D/NB