



TUBOMATIC H88 ES

Code: TUBH88ES

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H88 EL

Code: TUBH88EL

CRIMPING (STANDARD VOLUME CRIMPING)



ALSO AVAILABLE WITH PORTABLE DIES HOLDER



MAIN FEATURES - CARATTERISTICHE PRINCIPALI

- Ideal for any type of fitting
H88 ES
- ES3 touch-screen electronic control
H88 ES
- Back limit switch
H88 ES
- Electro-mechanical control
H88 EL
- Warning LED
H88 EL
- Vernier dial
H88 EL
- Ideal for your workshop

TECHNICAL DATA		
	H88 ES	H88 EL
CRIMPING FORCE	150 US TONS	150 US TONS
6 SPIRALS 2 PIECES	1"	1"
4 SP 2 PIECES	1" 1/2*	1" 1/2*
4 SH 2 PIECES	1" 1/4	1" 1/4
MAX Ø	88 mm (3.4") [†]	64 mm (2.5") [†]
CRIMPING/HOUR	680 [‡]	680 [‡]
DIE OPENING	Ø + 1.8"	Ø + 1.8"
90° FITTINGS	1" 1/4	1" 1/4
STANDARD VOLTAGE	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH
MOTOR POWER	4 Kw (5 Hp)	4 Kw (5 Hp)
DIMENSIONS LxWxH	27.5"x24.2"x25.1"	27.5"x26.5"x25.1"
WEIGHT WITHOUT OIL	386 Lbs	381 Lbs
OIL (NOT INCLUDED)	70 Lt. (18 US gal)	70 Lt. (18 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■

ACCESSORIES			
		H88 ES	H88 EL
CRIMPING SPEED CONTROL SYSTEM		■	-
PRESSURE CONTROL SYSTEM KIT		■	-
USB KIT		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-
MULTISTEP CRIMPING DIAMETERS		■	-
DISPENSER + PATENTED QUICK CHANGE		■	■
ELECTRIC PEDAL			
BASE		■	■
BACK MIRROR		■	■

Diameter (mm) ▶	10	12	14	16	19	22	25	29	34	38	42	46
H88 ES	60	60	60	60	60	60	60	70	70	85	85	85
H88 EL												

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - † WITH SPECIAL DIES Ø 54 MM UPON REQUEST - ‡ WITH SPECIAL DIES ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.