

TUBOMATIC H170 ES

Code: **TUBH170ES**

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H170 EL

Code: **TUBH170EL**

CRIMPING (STANDARD VOLUME CRIMPING)



MAIN FEATURES



H170 ES

H170 ES

H170 EL

H170 ES

H170 EL

H170 EL

TECHNICAL DATA

	H170 ES	H170 EL
CRIMPING FORCE	308 US TONS	308 US TONS
6 SPIRALS 2 PIECES	1" 1/2	1" 1/2
4 SH 2 PIECES	2"	2"
INDUSTRIAL HOSE	4"	4"
MAX Ø	170 mm (6.7") ♦	170 mm (6.7") ♦
CRIMPING / HOUR	865 ■	865 ■
DIE OPENING	Ø + 2.4"	Ø + 2.4"
90° FITTINGS	2"	2"
STANDARD VOLTAGE	Any 60HZ 3PH	Any 60HZ 3PH
MOTOR POWER	5.5 Kw (7 Hp) - A 10.74	5.5 Kw (7 Hp) - A 10.74
DIMENSIONS LxWxH	32.2"x31.9"x32.9"	32.2"x25.9"x32.9"
WEIGHT WITHOUT OIL	1102 Lbs	1102 Lbs
OIL (NOT INCLUDED)	110 Lt. (29 US gal)	110 Lt. (29 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■

ACCESSORIES

		H170 ES	H170 EL
PRESSURE CONTROL SYSTEM KIT		■	-
USB KIT		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-
MULTISTEP CRIMPING DIAMETERS		■	-
DISPENSER + PATENTED QUICK CHANGE		■	■
BASE		■	■
BACK MIRROR		■	■
CLEANING AND MAINTENANCE KIT		■	■
ELECTRIC PEDAL		■	■

Diameter (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73	77	86	90	96	103	106	111	116	121	126	131	
H170 ES																														
H170 EL	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100	120	120	150	120	130	130	130	130	130	130	130	130
	DIES LENGTH (mm)																													

♦ WITH SPECIAL DIES Ø 131 MM UPON REQUEST

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.