



TUBOMATIC H144 ES

Code: **TUBH144ES**

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H144 EL

Code: **TUBH144EL**

CRIMPING (STANDARD VOLUME CRIMPING)



MAIN FEATURES



Ideal for any type of fitting



ES3 touch-screen electronic control

H144 ES



Industrial hose crimp calculator

H144 ES



Warning LED

H144 EL



Back limit switch

H144 ES



Vernier dial

H144 EL



Electro-mechanical control

H144 EL



Ideal for your workshop

TECHNICAL DATA		
	H144 ES	H144 EL
CRIMPING FORCE	440 US TONS	440 US TONS
6 SPIRALS 2 PIECES	2" 1/2	2" 1/2
INDUSTRIAL HOSE	4"	4"
MAX Ø	144 mm (5.6")	144 mm (5.6")
CRIMPING / HOUR	703 [■]	703 [■]
DIE OPENING	Ø + 1.7"	Ø + 1.7"
90° FITTINGS	2"	2"
STANDARD VOLTAGE	Any 60HZ 3PH	Any 60HZ 3PH
MOTOR POWER	5.5 Kw (7.5 Hp) - A= 10,74	5.5 Kw (7.5 Hp) - A= 10,74
DIMENSIONS LxWxH	33"x30.3"x33.6"	33"x25.9"x33.6"
WEIGHT WITHOUT OIL	1213 Lbs	1210 Lbs
OIL (NOT INCLUDED)	110 Lt. (29 US gal)	110 Lt. (29 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■

ACCESSORIES			
		H144 ES	H144 EL
PRESSURE CONTROL SYSTEM KIT		■	-
USB KIT		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-
MULTISTEP CRIMPING DIAMETERS		■	-
DISPENSER + PATENTED QUICK CHANGE		■	■
BASE		■	■
BACK MIRROR		■	■
CLEANING AND MAINTENANCE KIT		■	■
ELECTRIC PEDAL			

Diameter (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73	77	86	90	96	103	106	111	116	121	126	131
	DIES LENGTH (mm)																												
H144 ES	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100	120	120	150	120	130	130	130	130	130	130	130
H144 EL	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100	120	120	150	120	130	130	130	130	130	130	130

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.