



TUBOMATIC H135 ES

Code: **TUBH135ES**

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H135 EL

Code: **TUBH135EL**


CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H135/E EL

Code: **TUBH135/EEL**

CRIMPING (STANDARD VOLUME CRIMPING)



MAIN FEATURES



Ideal for any type of fitting



ES3 touch-screen electronic control

H135 ES



Back limit switch

H135 ES



Electro-mechanical control

**H135 EL
H135/E EL**



Warning LED

H135 EL



Vernier dial

**H135 EL
H135/E EL**



Ideal for your workshop

| TECHNICAL DATA | | | |
|---|----------------------------|----------------------------|----------------------------|
| | H135 ES | H135 EL | H135/E EL |
| CRIMPING FORCE | 345 US TONS | 345 US TONS | 330 US TONS |
| 6 SPIRALS 2 PIECES | 2" | 2" | 2" |
| INDUSTRIAL HOSE | 3" | 3" | 3" |
| MAX Ø | 135 mm (5.3") [♦] | 120 mm (4.7") [♦] | 111 mm (4.3") [♦] |
| CRIMPING / HOUR | 865 [■] | 865 [■] | 271 [■] |
| DIE OPENING | Ø + 1.6" | Ø + 1.6" | Ø + 1.6" |
| 90° FITTINGS | 2" | 2" | 2" |
| STANDARD VOLTAGE | Any 60HZ 3PH | Any 60HZ 3PH | 230V 60HZ 1PH |
| MOTOR POWER | 5.5 Kw (7.5 Hp) - A= 10.64 | 5.5 Kw (7.5 Hp) - A= 10.64 | 4 Kw (5.5 Hp) |
| DIMENSIONS LxWxH | 32.2"x29.5"x32.2" | 32.2"x25.9"x32.2" | 30.7"x24.8"x28" |
| WEIGHT WITHOUT OIL | 1047 Lbs | 1036 Lbs | 704 Lbs |
| OIL (NOT INCLUDED) | 110 Lt. (29 US gal) | 110 Lt. (29 US gal) | 55 Lt. (14 US gal) |
| SETTABLE RE-OPENING TIME AFTER CRIMPING | - | ■ | - |
| SETTABLE CRIMPING TIME | - | ■ | - |

| ACCESSORIES | | | | |
|---|--|---------|---------|-----------|
| | | H135 ES | H135 EL | H135/E EL |
| PRESSURE CONTROL SYSTEM KIT | | ■ | - | - |
| USB KIT | | ■ | - | - |
| QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL | | ■ | - | - |
| MULTISTEP CRIMPING DIAMETERS | | ■ | - | - |
| DISPENSER + PATENTED QUICK CHANGE | | | | |
| BASE | | ■ | ■ | ■ |
| BACK MIRROR | | ■ | ■ | - |
| CLEANING AND MAINTENANCE KIT | | ■ | ■ | ■ |
| ELECTRIC PEDAL | | | | |

| Diameter (mm) | 10 | 12 | 14 | 16 | 19 | 22 | 25 | 29 | 34 | 38 | 42 | 46 | 50 | 54 | 58 | 63 | 69 | 73 |
|--|-------------------------|----|----|----|----|----|----|----|----|----|----|----|----|----|----|-----|-----|-----|
| H135 ES - H135 EL H135/E EL | DIES LENGTH (mm) | | | | | | | | | | | | | | | | | |
| | 60 | 60 | 60 | 60 | 60 | 60 | 60 | 70 | 70 | 85 | 85 | 95 | 95 | 95 | 95 | 100 | 100 | 100 |

♦ WITH SPECIAL DIES Ø 104 MM UPON REQUEST ■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.