



TUBOMATIC H130 ES

Code: TUBH130ES

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H130 EL

Code: TUBH130EL

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H130/E EL

Code: TUBH130/EEL

CRIMPING (STANDARD VOLUME CRIMPING)



MAIN FEATURES



Ideal for any type of fitting



ES3 touch-screen electronic control

H130 ES



Back limit switch

H130 ES



Electro-mechanical control

H130 EL
H130/E EL



Warning LED

H130 EL



Vernier dial

H130 EL
H130/E EL



Ideal for your workshop

TECHNICAL DATA			
	H130 ES	H130 EL	H130/E EL
CRIMPING FORCE	210 US TONS	210 US TONS	275 US TONS
6 SPIRALS 2 PIECES	1" 1/4	1" 1/4	1" 1/4
4 SP 2 PIECES	2"	2"	2"
INDUSTRIAL HOSE	3"	3"	3"
MAX Ø	130 mm (5.1") [♦]	124 mm (4.9") [♦]	111 mm (4.3") [♦]
CRIMPING / HOUR	780 [■]	780 [■]	246 [■]
DIE OPENING	Ø + 1.3"	Ø + 1.3"	Ø + 1.3"
90° FITTINGS	2"	2"	2"
STANDARD VOLTAGE	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH
MOTOR POWER	4 Kw (5.5 Hp)	4 Kw (5.5 Hp)	2.2 Kw (2.9 Hp)
DIMENSIONS LxWxH	29.9"x27.1"x28.7"	29.9"x26.5"x28.1"	26.2"x23.1"x26"
WEIGHT WITHOUT OIL	650 Lbs	650 Lbs	454 Lbs
OIL (NOT INCLUDED)	65 Lt. (17 US gal)	65 Lt. (17 US gal)	22 Lt. (6 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■	-
SETTABLE CRIMPING TIME	-	■	-

ACCESSORIES				
		H130 ES	H130 EL	H130/E EL
PRESSURE CONTROL SYSTEM KIT		■	-	-
USB KIT		■	-	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-	-
MULTISTEP CRIMPING DIAMETERS		■	-	-
DISPENSER + PATENTED QUICK CHANGE		■	■	■
BASE		■	■	■
BACK MIRROR		■	■	-
CLEANING AND MAINTENANCE KIT		■	■	■
ELECTRIC PEDAL		■	■	■

Diameter (mm)	10	12	14	16	19	22	25	29	34	38	42	46	50	54	58	63	69	73
H130 ES																		
H130 EL - H130/E EL	60	60	60	60	60	60	60	70	70	85	85	95	95	95	95	100	100	100
	DIES LENGTH (mm)																	

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - ♦ WITH SPECIAL DIES Ø 104 MM UPON REQUEST
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.