

TUBOMATIC H88 ES

Code: **TUBH88ES**

CRIMPING (STANDARD VOLUME CRIMPING)



TUBOMATIC H88 EL

Code: **TUBH88EL**

CRIMPING (STANDARD VOLUME CRIMPING)











ALSO AVAILABLE WITH
PORTABLE DIES HOLDER



MAIN FEATURES - CARATTERISTICHE PRINCIPALI

						
Ideal for any type of fitting	ES3 touch-screen electronic control	Back limit switch	Electro-mechanical control	Warning LED	Vernier dial	Ideal for your workshop
H88 ES	H88 ES	H88 ES	H88 EL	H88 EL	H88 EL	

TECHNICAL DATA		
	H88 ES	H88 EL
CRIMPING FORCE	150 US TONS	150 US TONS
6 SPIRALS 2 PIECES	1"	1"
4 SP 2 PIECES	1" 1/2 [•]	1" 1/2 [•]
4 SH 2 PIECES	1" 1/4	1" 1/4
MAX Ø	88 mm (3.4") [♦]	64 mm (2.5") [♦]
CRIMPING/HOUR	680 [■]	680 [■]
DIE OPENING	Ø + 1.8"	Ø + 1.8"
90° FITTINGS	1" 1/4	1" 1/4
STANDARD VOLTAGE	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH
MOTOR POWER	4 Kw (5 Hp)	4 Kw (5 Hp)
DIMENSIONS LxWxH	27.5"x24.2"x25.1"	27.5"x26.5"x25.1"
WEIGHT WITHOUT OIL	386 Lbs	381 Lbs
OIL (NOT INCLUDED)	70 Lt. (18 US gal)	70 Lt. (18 US gal)
SETTABLE RE-OPENING TIME AFTER CRIMPING	-	■
SETTABLE CRIMPING TIME	-	■

ACCESSORIES			
		H88 ES	H88 EL
PRESSURE CONTROL SYSTEM KIT		■	-
USB KIT		■	-
QUALITY CHECK: PRESSURE AND DIAMETER COMBINED CONTROL		■	-
MULTISTEP CRIMPING DIAMETERS		■	-
DISPENSER + PATENTED QUICK CHANGE		■	■
ELECTRIC PEDAL			
BASE		■	■
BACK MIRROR		■	■

Diameter (mm) ▶	10	12	14	16	19	22	25	29	34	38	42	46
H88 ES	DIES LENGTH (mm)											
H88 EL	60	60	60	60	60	60	60	70	70	85	85	85

■ THEORETICAL WITH 1/2" Δ Ø 6 MM HOSE - ♦ WITH SPECIAL DIES Ø 54 MM UPON REQUEST - - ♦ WITH SPECIAL DIES
ALL CAPACITIES INDICATED DEPEND ON THE KIND OF FITTING USED

Product specifications could be modified without prior notice.