

### TF3/E

Code: TAGLTF3D/E

CUTTING



### TF2/E

Code: TAGLTF2D/E

CUTTING



### TF1/E

Code: TAGLTF1D/E

CUTTING



## MAIN FEATURES



Safety protections



Suction connection



Serrated blade



Manually operated



Ideal for on-site service



Recessed blade for a greater safety



Also available in 12V - 24V

TF1/E  
TF2/E  
TF3/E

### TECHNICAL DATA

	TF3/E	TF2/E	TF1/E
6 SPIRALS	2"	1" 1/2	1"
4 SPIRALS	-	2"	1" 1/4
2 BRAIDS	-	2"	1" 1/4
MAX Ø (OD)	3.3"	2.9"	2.3"
REVOLUTIONS/MINUTE	2900	2900	2900
BLADE Ø	350 mm (13.7")	250 mm (9.8")	250 mm (9.8")
STANDARD VOLTAGE	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH	Any 60HZ 3PH/1PH
DIMENSIONS LxWxH	29.9"x20.9"x20"	25.5"x27.5"x16.5"	20.6"x25.9"x17.5"
WEIGHT	131 Lbs	97 Lbs	66 Lbs
MOTOR POWER	3 Kw (4 Hp)	3 Kw (4 Hp)	1.1 Kw (1.5 Hp)

### ACCESSORIES

	TF3/E	TF2/E	TF1/E
CENTERING DEVICE + METER COUNTER (MAX 2")			-

COMPACT AND INEXPENSIVE EQUIPMENT, IDEAL FOR ON-SITE SERVICE