



BC 800/W - ES

Code: BC800/WES

TESTING

WITH PNEUMO-HYDRAULIC MULTIPLIER;
IDEAL FOR PALLETISED HOSE COILS



MAIN FEATURES



Touch-screen
electronic control



Internal lighting



Shock-proof
testing windows



Temperature warning signal



USB connection
configuration



PDF files printing

TECHNICAL DATA

STATIC PRESSURE	800 Bar (11600 Psi)
IMPULSE PRESSURE	800 Bar (11600 Psi)
MIN. STARTING PRESSURE	30 Bar (435 Psi)
PRESSURE CONTROL	Automatic
TEST	Semi-automatic
TYPE OF DRIVE	Pneumatic Intensifier
TESTING LIQUID	Fluid
N° MANIFOLDS	2
N° CONNECTIONS PER MANIFOLD	1 x 1/2" BSP
SAE MANIFOLD CONNECTIONS	1 x 2" 6000 PSI
LIQUID FILLING	Semi-automatic
FILLING FLOW	25 Lt./min. (6.5 US gal/min.)
PRESSURE PUMP FLOW	10.5 Lt./min. (3 US gal/min.)
HOSE EMPTING SYSTEM	Semi-automatic
PRESSURE DISCHARGE	Automatic
MECHANICAL SAFETY DEVICE	Automatic
ELECTRIC SAFETY DEVICE	Automatic
STANDARD CHAMBER DIMENSIONS	74.8"x59"x28.3"
BENCH DIMENSIONS	103.1"x70"x60.2"
TANK	250 Lt. (66 US gal)
WEIGHT WITHOUT OIL	2127 Lbs
STANDARD VOLTAGE	Any 60HZ 3PH

INCLUDED ACCESSORIES

SUCTION FILTER

DELIVERY FILTER

INTERNAL OIL PROTECTING MESH

PRESSURE PEAK MEMORY

LEVEL WARNING SIGNAL

OPTIONAL

ADAPTORS



PC CONNECTION



INDUSTRY 4.0 KIT

4.0

CHAMBER AND COMPONENTS ALSO AVAILABLE IN STAINLESS
STEEL FOR WATER TESTS