



BC 1200 ES/F

Code: BC1200ES/F

TESTING

PROVIDED WITH QUICK COUPLINGS AND A HIGH NUMBER OF NIPPLE THREADS AND HOLES FOR SAE FLANGES



PLATFORM FOR TESTING HOSE COILS ON PALLET



FLEXIBLE CONFIGURATION OF THE MOBILE MANIFOLD

MAIN FEATURES



Touch-screen electronic control



Internal lighting



Shock-proof testing windows



Sliding manifolds



Temperature warning signal



Automatic door opening



USB connection configuration



PDF files printing

TECHNICAL DATA	
STATIC PRESSURE	1200 bar (17400 Psi)
IMPULSE PRESSURE	1200 bar (17400 Psi)
MIN. STARTING PRESSURE	30 Bar (435 Psi)
PRESSURE CONTROL	Automatic
TEST	Automatic
TYPE OF DRIVE	Pneumatic Intensifier
TESTING LIQUID	Fluid
N° MANIFOLDS	2
N° CONNECTIONS PER MANIFOLD	1
LIQUID FILLING	Automatic
FILLING FLOW	25 Lt./min. (6.5 US gal/min)
PRESSURE PUMP FLOW	1.55 Lt./min. (0.4 US gal/min)
HOSE EMPTYING SYSTEM	Automatic
PRESSURE DISCHARGE	Automatic
DOOR ELECTRIC SAFETY DEVICE	Automatic
PRESSURE DISPLAY	Digital
STANDARD CHAMBER DIMENSIONS	157.4"x50.7"x35"
BENCH DIMENSIONS	161.4"x55.1"x80.7"
AIR CONSUMPTION	1500 Lt./min. (396 US gal/min)
TANK	150 Lt. (39 US gal)
STANDARD VOLTAGE	Any 60HZ 3PH
WEIGHT WITHOUT OIL	3589 Lbs

INCLUDED ACCESSORIES	
SUCTION FILTER	
DELIVERY FILTER	
INTERNAL OIL PROTECTING MESH	
SHELVES FOR TOOLS	
PRESSURE PEAK MEMORY	
LEVEL WARNING SIGNAL	
OPTIONAL	
PRESSURE CONTROL	
ADAPTORS	
WASHING DEVICE	
PC CONNECTION	
INDUSTRY 4.0 KIT	4.0