

BC 1500 E/WATER

Code: BC1500E/WATER

TESTING

PROVIDED WITH ONE Ø 1/4" BSP QUICK CONNECTOR AND PNEUMO-HYDRAULIC PUMP



MAIN FEATURES



Low and high pressure mode



Manually operated



Shock-proof testing windows



Water tests

TECHNICAL DATA	
LOW PRESSURE MODE	10 Bar (145 Psi) ÷ 70 Bar (1015 Psi)
HIGH PRESSURE MODE	70 Bar (1015 Psi) ÷ 1500 Bar (21756 Psi)
PRESSURE CONTROL	Manual
TEST	Manual
TYPE OF DRIVE	Pneumatic / Electric Intensifier
TESTING LIQUID	Water
N° MANIFOLDS	1
N° CONNECTIONS PER MANIFOLD	1x1/4" BSP Quick Connection
LIQUID FILLING	Manual
FILLING FLOW	4 Lt/Min. (1.1 US gal/min.)
LOW / HIGH PRESSURE PUMP FLOW	4 Lt/Min. (1.1 US gal/min.) 1.55 Lt/Min. (0.4 US gal/min.)
PRESSURE DISCHARGE	Manual
STANDARD CHAMBER DIMENSIONS	78.7"x33.3"
BENCH DIMENSIONS	107.5"x41.5"x47.7"
WEIGHT WITHOUT WATER	608.5 Lbs
PRESSURE GAUGE	Analogic
STANDARD VOLTAGE	400V 50Hz 3PH
MOTOR POWER	1.5 Kw (2 Hp)

INCLUDED ACCESSORIES
DELIVERY FILTER
OPTIONAL
ADAPTORS: 3/8" - 1/2" - 3/4" - 1" - 1 1/4" - 1 1/2" - 2"
PRESSURE REPORT KIT

CHAMBER AND COMPONENTS MADE IN STAINLESS STEEL