

UNISPEED USFL 24/37 ES

Code: UNISUSFL2437ES

FLARING & PREASSEMBLY



UNISPEED USFL 24/37 ES 6/18

Code: UNISFL2437ES618

FLARING & PREASSEMBLY

PATENT PENDING CYLINDER



MAIN FEATURES



DIN2353 rings preassembly



37° flaring



Touch-screen electronic control



Ideal for volume production



Equipped with wheels








Front tool-holder compartment



Ideal for the automotive industry

USFL24/37 ES 6/18

	TECHNICAL DATA	
	USFL 24/37 ES	USFL 24/37 ES 6/18
24° PREASSEMBLY	6→42x4 mm	6→18x2 mm
37° FLARING	1/4" → 1" 1/2 x 0.15"	1/4" → 5/8" x 0.08"
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
WEIGHT WITHOUT OIL	330 Lbs	291 Lbs
DIMENSIONS LxWxH	23"x23.6"x45.2"	31.8"x31.4"x42.3"
STANDARD VOLTAGE	Any 60HZ 3PH	Any 60HZ 3PH
MOTOR POWER	1.5 Kw (2 Hp)	0.75 Kw (1 Hp)
OIL (NOT INCLUDED)	15 Lt. (4 US gal)	13 Lt. (3.5 US gal)

	OPTIONAL		
		24/37 ES	24/37 ES 6/18
ELECTRIC PEDAL		<input type="checkbox"/>	<input type="checkbox"/>
37° FLARING BLOCK		<input type="checkbox"/>	<input type="checkbox"/>
37° FLARING BLOCK		<input type="checkbox"/>	<input type="checkbox"/>
TOOL HOLDER (6→42)		<input type="checkbox"/>	<input type="checkbox"/>
TOOL HOLDER (6→18)		<input type="checkbox"/>	<input type="checkbox"/>

USFL 24/37 ES
EQUIPPED WITH A DOUBLE WORKING LEVEL:
UPPER LEVEL FOR BENDS UP TO 180°,
LOWER LEVEL FOR STANDARD TUBES
*DOTATA DI DOPPIO LIVELLO DI LAVORAZIONE:
LIVELLO SUPERIORE PER CURVE FINO A 180°,
LIVELLO INFERIORE PER TUBI STANDARD*

USFL 24/37 ES 6/18
SUITABLE FOR TUBES WITH EXTREME BENDS
UP TO 180° (SHAPED RIGID TUBES,
STEEL AND HOSE COMBINED CONNECTIONS)
*ADATTA A TUBI CON CURVE ESTREME FINO A 180°
(TUBI RIGIDI SAGOMATI,
TUBI COMBINATI FLESSIBILI-RIGIDI)*



37° FLARING TOOLS:
they are supplied according to UNI ISO 8434-2 and DIN 3949 regulations

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

Product specifications could be modified without prior notice.