

UNISPEED USFL/01 MAN

Code: USFLMAN

FLARING & PREASSEMBLY



UNISPEED USFL 015 MAN

Code: USFL015MAN

PREASSEMBLY

SUITABLE TO BE FIXED TO ANY VICE
AND FOR LL, L, S SERIES TOOLS
AND FOR TUBES WITH EXTERNAL Ø 6-15 MM.



MAIN FEATURES



DIN2353 rings preassembly

Premontaggio anelli DIN2353



37° flaring with the addition of
a dedicated steel flaring block

Svasatura 37° mediante aggiunta
di blocco in acciaio dedicato



Ideal for on-site service

Ideale per il service



Manually operated

Azionamento manuale

USFL/01 MAN

TECHNICAL DATA		
	USFL/01 MAN	USFL 015 MAN
24° PREASSEMBLY	6→42x4 mm	6S - 15L
37° FLARING	1/4 →1" 1/2 x 0.15"	-
MATERIALS	AISI 316 TI - ST 37.4	AISI 316 TI - ST 37.4
WEIGHT	84 Lbs	26 Lbs
DIMENSIONS LxWxH	13.7"x15.7"x10.6"	11.2"x4.1"x4.1"
LEVEL LENGHT	-	31.4"

USFL/01 MAN: 37° FLARING TOOLS SUPPLIED ACCORDING TO UNI ISO 8434-2
AND DIN 3949 REGULATIONS

OPTIONAL			
		USFL/01 MAN	USFL/015 MAN
37° FLARING BLOCK (6→42)		■	-
TOOL HOLDER (6→42)		■	-

EQUIPMENT SUITABLE TO PROCESS RIGID TUBES
IN STAINLESS (AISI 316 TI) AND CARBON (ST 37.4) STEEL

MANUAL PREASSEMBLING TOOL

Manual preassembling tool (6→42 mm)



TEMPLATE FOR PREASSEMBLING TOOL CONTROL

Template for preassembling tool control (6→42 mm)

